RICOH COMPANY, LTD

RICOH

imagine. change.

Color MFP (Electrophotography)

RICOH IM C300F



Functional unit

Per product

System boundary

■ final products □ intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Product name:RICOH IM C300F Main specifications: Color MFP (Electrophotography) Print Speed : 30 prints/minute (A4) Maximum Paper Size : 8.5" x 14" Included Units in Assessment : Automatic Reversing Document Feeder, Automatic Duplexing Unit

Company Information

RICOH COMPANY, LTD

Tel:(03) 3777-8111

Registration#	JR-AI-24064E	
PCR number	PA-590000-AI-08	
PCR name	Imaging input and/or output equipment	
Publication date	3/29/2024	
Verification date	3/15/2024	
Verification method	System certificaion	
Verification#	JV-AI-24064	
Expiration date	3/14/2029	
PCR review was conducted by:		
Approval date	9/1/2023	
PCR review	Masayuki Kanzaki	
panel chair	(SuMPO)	
Third party verifier*		

Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24064E



EcoLeaf

Type III Environmental Declaration (EPD) Registration number : JR-AI-24064E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA) 0% 20% 40% 60% 80% 100% 8% 640 Global warming IPCC2013 GWP100a kg-CO2eq 63% 3% 24% 1% 1% 0.52 Acidification kg-SO2eq 66% 24% 7% 1% 0% 0% 22% 78% 0% 0.37 **Resources consumption** kg-Sbeq Raw material acquisition Production Distribution Use & maintenance End-of-Life stage Raw material Use & Parameter Unit Total Distribution maintenance acquisition Production End-of-Life Global warming IPCC2013 GWP100a kg-CO2eq 6.4E+02 4.1E+02 5.3E+01 2.2E+01 1.6E+02 7.9E+00 Acidification kg-SO₂eq 5.2E-01 3.5E-01 5.8E-03 3.6E-02 1.3E-01 7.2E-03 9.1E-05 Resources consumption kg-Sbeq 3.7E-01 2.9E-01 9.9E-05 8.1E-02 1.9E-05

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable material resources	4.0E+01	kg		
Renewable material resources	7.7E+01	kg		

3. Material composition			
Material		Unit	
SUS	1.2E+00	kg	
Aluminum	5.3E-01	kg	
Ordinary steel	1.9E+01	kg	
Other metals	2.2E+00	kg	
Thermoplastic resin	2.2E+01	kg	
Thermosetting resin	4.0E-01	kg	
Glass	1.1E+00	kg	
Rubber	6.6E-01	kg	
Paper	9.1E+00	kg	
Lubricant	4.6E-03	kg	
Mounting circuit board	1.9E+00	kg	
Wood	1.0E-04	kg	

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

Products selected in the scenario used for load calculation

--Multifunction device (EP)

Product destination: DOM

• Expected usage period: 5 years

• Estimated number of sheets:135,000 sheets ※

*Compatible with International Energy Star Program Ver.3.0

-The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive. Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number:SGS-CN18/20330

JQA-E-70001 https://jp.ricoh.com/sustainability/environment/management/iso

7. Assumptions of secondary data used IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO v1.13 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-24064E