RICOH COMPANY, LTD

RICOH

imagine. change.

Black & White MFP (Electrophotography)

IM 370F (for NA)





Functional unit

Per product

System boundary

Tel:(03) 3777-8111

■ final products □ intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Product name:IM 370F Product destination: NA Main specifications: Black & White MFP (Electrophotography) Print Speed : 37 prints/minute (A4) Maximum Paper Size : A4 Included Units in Assessment : Automatic Reversing Document Feeder, Automatic Duplexing Unit **Company Information** RICOH COMPANY,LTD

Registration#	JR-AI-23227E			
PCR number	PA-590000-AI-07			
PCR name	Imaging input and/or output equipment			
Publication date	7/31/2023			
Verification date	7/25/2023			
Verification method	Product-by-product			
Verification#	JV-AI-23227			
Expiration date	7/24/2028			
PCR review was conducted by:				
Approval date	4/27/2023			
PCR review	Masayuki Kanzaki			
panel chair	(SuMPO)			
Third party verifier*				
	Takahiro Atou			

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23227E



EcoLeaf

Type III Environmental Declaration (EPD) Registration number : JR-AI-23227E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)										
			0%	2	0%	40%	60	% 80)%	100%
Global warming IPCC2013 GWP100a	540	kg-CO2eq			52%		<mark>3%</mark> 3%	31%		10%
Acidification	0.36	kg-SO2eq			65%			1 <mark>%6%</mark>	20% 0%	<mark>8%</mark> 0% 0%
Resources consumption	0.17	kg-Sbeq					97%		0%	0% 0% 3%
Raw material acquisition Distribution End-of-Life									ce	
stage			Raw m	aterial				Use &		
Parameter	Unit	Total	acqui	sition	Production	ו Di	istribution	maintenanc	e Er	nd-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	5.4E+02	2.8E	+02	1.8E+01	L 1	.7E+01	1.7E+02	5	.5E+01
Acidification	kg-SO ₂ eq	3.6E-01	2.38	E-01	4.3E-03	2	2.2E-02	7.0E-02	2	.7E-02
Resources consumption	kg-Sbeq	1.7E-01	1.6	-01	4.5E-05	7	7.2E-05	4.2E-03	2	.1E-05

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	3.1E+01	kg			
Renewable material resources	5.1E+01	kg			

3. Material composition				
Material		Unit		
SUS	0.30	kg		
Aluminum	0.25	kg		
Ordinary steel	19	kg		
Other metals	1.8	kg		
Thermoplastic resin	17	kg		
Thermosetting resin	0.93	kg		
Glass	0.87	kg		
Rubber	0.19	kg		
Paper	6.5	kg		
Lubricant	0.0012	kg		
Mounting circuit board	0.85	kg		
Wood	0.00027	kg		

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

Products selected in the scenario used for load calculation

--Multifunction device (EP)

Product destination: NA ※

** Transportation scenarios are for China, Thailand, and Ricoh Group.from three production sites in Japan, North America, Europe, on transportation routes to the five poles of China, Oceania and Japan transport load calculate the weighted average of transportation activity per kg of product from the total calculated using the annual production volume for each pole. Then, it is used as a transportation unit of calcuration.

- Expected usage period: 5 years
- Estimated number of sheets:201600 sheets ※

*Compatible with International Energy Star Program Ver.3.0

-The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number:BSI-EMS646026 JQA – E-70001

https://jp.ricoh.com/sustainability/environment/management/iso

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO v1.13 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-23227E